



WATER RESISTANT



STAIN RESISTANT



ANTIBACTERIAL



WARRANTY



FASTNESS TO LIGHT



AZO DYE FREE



SOFT TOUCH



REACH COMPLIANT

Composición Composition Composition		100% Solution Dyed Acrylic	
Ancho Width Laize		160 cm	
Peso Weight Poids		280 g/m²	
Rapport Repeat Rapport	Ancho Width Laize	-	
	Largo Length Longueur	-	
Martindale UNE-EN ISO 12947 - BS 2543		40.000	
Pilling UNE-EN ISO 12945-2		4	
Solidez a la luz Fastness to light Résistance à la lumière ISO 105-B02		7-8	
Costuras Seam slippage Coutures de fils	Urd. Warp Chaîne	<5 mm	
	Trama Weft Trame	<4 mm	
Encogimiento al lavado (30°C) Shrinkage to washing Retrait au lavage	Urd. Warp Chaîne	≤1,5%	
	Trama Weft Trame	≤1%	
Solidez al frote Fastness to rubbing Résistance au frottement	Seco Dry Sec	4-5	
	Húmedo Wet Humide	4	
Orientación Orientation Orientation			
Aplicaciones Application Application			
Acabado Finish Finition	 Teflon acabado antimanchas y antibacterial Teflon with and mildew resistant treatment Téflon avec traitement anti taches et antibactérien		
Recomendaciones Recommendations Recommandations	Para su limpieza, emplear jabon natural en agua tibia. Clean fabrics with natural soaps in lukewarm water. Se utilizar lejía con moderacion. No lavar en seco Bleach may be used, in moderation . Do not dry-cleanl.		
Instrucciones de lavado Care instructions Entretien			
 Lavar a máquina suave max. 30°C con colores similares Wash max. 30°C, mild process with similar colours Laver en machine max 30°C avec couleurs similaires  Se puede usar lejía Bleach permitted Eau de Javel tolérée  No secar en secadora Do not tumble dry Ne pas sécher au sèche-linge  Planchar max. 110°C Iron at max. 110°C Repasser max. 110°C  No limpiar en seco Do not dry clean Ne pas laver à sec			