



VALQUIDIA

clean
only with water

MANUEL REVERT



EASY CLEAN



FIRE RETARDANT
BS 5852 part 1



AZO DYE FREE



SOFT TOUCH



REACH COMPLIANT

Composición Composition Composition		100% PES	
Ancho Width Laize		140 cm	
Peso Weight Poids		385 g/m ²	
Rapport Repeat Rapport	Ancho Width Laize	-	
	Largo Length Longueur	-	
Martindale UNE-EN ISO 12947 - BS 2543		>60.000	
Pilling UNE-EN ISO 12945-2		4	
Solidez a la luz Fastness to light Résistance à la lumière ISO 105-B02		4-5	
Costuras Seam slippage Coutures de fils	Urd. Warp Chaîne	<3 mm	
	Trama Weft Trame	<3 mm	
Encogimiento al lavado (30°C) Shrinkage to washing Retrait au lavage	Urd. Warp Chaîne	≤2%	
	Trama Weft Trame	≤2%	
Solidez al frote Fastness to rubbing Résistance au frottement	Seco Dry Sec	4-5	
	Húmedo Wet Humide	4	
Orientación Orientation Orientation			
Aplicaciones Application Application		 TAPIZADOS DECORACIÓN	
Acabado Finish Finition	Tratamiento antimanchas Stain repellent treatment Traitement anti-taches		
Recomendaciones Recommendations Recommandations	No exponer directamente a la luz solar. Do not expose to direct sunlight. Para su limpieza, emplear un suave paño humedecido en agua jabonosa. Use a soft cloth dampened in soapy water for its cleaning. No utilizar disolventes, lejía o detergentes agresivos. El jabón debe ser neutro. Do not use solvents, bleach or harsh detergents. Soap must be natural.		
Instrucciones de lavado Care instructions Entretien			
Lavar a máquina suave max. 30°C con colores similares Wash max. 30°C, mild process with similar colours Laver en machine max 30°C avec couleurs similaires No blanquear (lejía / alternativos) Do not bleach (bleach / alternatives) Ne pas blanchir (lejía / alternatifs) No secar en secadora Do not tumble dry Ne pas sécher au sèche-linge No planchar Do not iron Ne pas repasser Puede limpiarse en seco. Proceso suave Can be dry clean, mild process Peut se laver à sec			